


DISCHARGE

2" NPT





1. SYSTEM DESIGNED FOR INDOOR INSTALLATION.

GPM	PSI	PSI
TOTAL FLOW	TOTAL DISCHARGE PRESSURE	AVAILABLE PRESSURE
	TOTAL SYSTEM CAPACITY	

ALL BOLTING AND ANCHORAGE TO BE IN COMPLIANCE WITH LOCAL CODES AND ANY

SEISMIC REQUIREMENTS.

	2	P-1	GOULDS	ESV	10SVG-2			2	3500	460/60/3	TEFC P.E.
	ITEM	TAG	MANUFACTURER	SERIES	MODEL	GPM	TDH	HP	RPM	VOLTS/HZ/PH	ENCLOSURE
PUMP SCHEDULE											

10	-	-	-
9	-	-	-
8	-	-	-
7	-	-	-
6	-	-	-
5	-	-	-
4	2	-	APOLLO SINGLE UNION BALL VALVE MODEL 70LF-308-01 - 2"
3	1	-	BONOMI IN-LINE CHECK VALVE - 2"
2	1	P-1	GOULDS ESV MULTI-STAGE PUMP MODEL 10SVG-2
1	1	-	TECHNOLOGIC INTELLIGENT PUMP CONTROLLER
ITEM	QTY	TAG	DESCRIPTION

EQUIPMENT SCHEDULE

PROJECT NAME:

CUSTOMER:

CHECKED BY APPROVED BY

HAYWARD, CALIFORNIA DRAWING TITLE:

DRAWN BY DATE ACD 04/03/19 TOLERANCES UNLESS OTHERWISE SPECIFIED

FMV1-3LH VARIABLE SPEED SIMPLEX PRESSURE BOOSTER

SUCTION

2" NPT

LISTED PACKAGED PUMPING SYSTEMS & HEAT TRANSFER SYSTEMS

THIS DRAWING AND THE INFORMATION DEPICTED THEREIN IS THE PROPERTY OF FLOWTHERM SYSTEMS, A DWISION OF CHC. COPIES ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASIS FOR MANUFACTURING OR SALE OF PRODUCT WITHOUT PRIOR WRITTEN PERMISSION OF CHC.

APPROXIMATE OPERATING WEIGHT: 225 LBS.

APPROXIMATE SHIPPING WEIGHT:

= DENOTES CONTRACTOR POINT OF CONNECTION

(1) SINGLE POINT POWER CONNECTION AT CONTROL PANEL.

(3) ASSEMBLED SYSTEM TO BE PAINTED WITH INDUSTRIAL MACHINE ENAMEL PRIOR TO

(2) HYDRO PRESSURE CHECK AT 125 PSI.

220 LBS.

RIGHT END VIEW

SHIPMENT.

SCALE 1" = 1'-0" DRAWING No. FMV1-3LH